



FEMMINA DIRITTA GAS CILINDRICO - OGIVA 60°



CODICE	Diametro interno tubo		Filettatura F	Dimensioni mm				
	Pollici	DN		C	H	L	G	D
EC02212	1/8"	3	1/8"-28	14	15	29	5	3
EC02213	1/8"	3	1/4"-19	17	16,5	31	5	4
EC03212	3/16"	5	1/8"-28	14	18	44	4,3	4
EC03213	3/16"	5	1/4"-19	19	18	44	5	5
EC04212	1/4"	6	1/4"-19	19	18	47	5	5
EC04213	1/4"	6	3/8"-19	22	20	48	7	7,5
EC05212	5/16"	8	3/8"-19	22	20	48	7	7,5
EC06212	3/8"	10	3/8"-19	22	20	50	7	7,5
EC06213	3/8"	10	1/2"-14	27	22	52	7	10
EC08212	1/2"	13	1/2"-14	27	23	56	7	10
EC08213	1/2"	13	5/8"-14	30	23	56	9	12,5
EC08292	1/2"	13	3/4"-14	32	25	58	9	15
EC10212	5/8"	16	5/8"-14	30	23	59	9	12,5
EC10213	5/8"	16	3/4"-14	32	25	61	9	15
EC12212	3/4"	19	3/4"-14	32	26	67	9	15
EC12213	3/4"	19	1"-11	41	26	67	10	21
EC16212	1"	25	1"-11	41	27	82	10	21
EC16213	1"	25	1.1/4"-11	50	30	85	11	27
EC20212	1.1/4"	32	1.1/4"-11	50	30	91	11	27
EC20213	1.1/4"	32	1.1/2"-11	55	34	95	11	33
EC24212	1.1/2"	38	1.1/2"-11	55	35	106	11	33
EC24213	1.1/2"	38	2"-11	70	36	107	15	44
EC32212	2"	51	2"-11	70	36	112	15	44

I raccordi presenti in questa pagina sono fornibili anche in **ACCIAIO INOX AISI 316**
Il codice cambia alla quinta cifra come nell'esempio:

EC	08	2	01
EC	08	8	01

> codice raccordo standard

> codice stesso raccordo in acciaio inox AISI 316

