



## FEMMINA 45° JIC - SVASATA 74°



CODICE	Diametro interno tubo		Filettatura F	Dimensioni mm					
	Pollici	DN		C	H	L	K	G	D
EC03238	3/16"	5	7/16"-20	15	34	60	13	9	4
EC04238	1/4"	6	7/16"-20	15	37	66	13	9	4
EC04239	1/4"	6	1/2"-20	17	38	67	13	9,5	5,5
EC04240	1/4"	6	9/16"-18	19	39	67	15	10	7
EC052J7	5/16"	8	1/2"-20	17	46	74	16	9,5	5,5
EC05238	5/16"	8	9/16"-18	19	46	74	16	10	7
EC06238	3/8"	10	9/16"-18	19	51	81	17	10	7
EC06239	3/8"	10	5/8"-18 SAE*	22	50	81	18	-	-
EC06240	3/8"	10	3/4"-16	24	53	84	19	11	10
EC062J8	3/8"	10	7/8"-14	27	56	86	21	13	12
EC08238	1/2"	13	3/4"-16	24	62	98	22	11	10
EC08239	1/2"	13	7/8"-14	27	63	96	23	13	12
EC08240	1/2"	13	1.1/16"-12	32	65	98	26	14,5	15
EC10238	5/8"	16	7/8"-14	27	77	113	25	13	12
EC10239	5/8"	16	1.1/16"-12	32	78	114	26	14,5	15
EC122J7	3/4"	19	7/8"-14	27	85	126,5	31,5	-	-
EC12238	3/4"	19	1.1/16"-12	32	86	127	33	14,5	15
EC12240	3/4"	19	1.3/16"-12	36	88	129	35	15	18
EC12239	3/4"	19	1.5/16"-12	41	91	132	37	15,5	21
EC16239	1"	25	1.1/16"-12	32	106	161,5	38,5	-	-
EC16238	1"	25	1.5/16"-12	41	107	162	40	15,5	21
EC16240	1"	25	1.5/8"-12	50	111	166	43	16	27,5
EC20238	1.1/4"	32	1.5/8"-12	50	135	196	52	16	27,5
EC20239	1.1/4"	32	1.7/8"-12	55	140	201	57	18,5	32
EC24238	1.1/2"	38	1.7/8"-12	55	161	231	57	18,5	32
EC32238	2"	51	2.1/2"-12	70	205	281	66	26	44

\* Svasatura 90°

I raccordi presenti in questa pagina sono fornibili anche in **ACCIAIO INOX AISI 316**  
Il codice cambia alla quinta cifra come nell'esempio:

EC	08	2	01
EC	08	8	01

&gt; codice raccordo standard

&gt; codice stesso raccordo in acciaio inox AISI 316

